



Taylor-Wharton
Since 1742

LNG FUEL TANKS

Superior Pressure Management

- Enhanced pressure control circuit
- Precise, responsive pressure management

Vacuum Technology

- Superior vacuum maintenance system
- Super insulation throughout the annular space

Reliable & Durable

- Reliable complete fill process
- Dependable accurate liquid level gauge
- All cryogenic rated components

Construction & Design

- Leak-free piping by design
- Minimized pipe thread connections
- 100% Stainless Steel Tubing
- Voltage regulated and temperature compensated liquid level gauge
- Externally mounted "high resolution" pressure gauge
- Externally mounted fill and vent connections

Available Accessories

- High capacity, engine coolant driven, vaporizer (with 300 psig safety relief valve)
- Final line gas regulator with mounting bracket
- 12-volt, normally closed, fuel line solenoid valve with mounting bracket

CREATING
SIMPLE
EFFECTIVE
LNG SOLUTIONS



Tank Specifications

MODELS		LNG-119V
Gross Volume	gal. L.	119 450
Diameter	in. mm.	26 650
Length (overall)	in. mm.	76 1930
Weight (empty)	lbs. kg.	530 240
Maxium operating Pressure	psi bar	230 15.9
Pressure Relief Valve	psi bar	230 15.9
Secondary Relief valve	psi bar	350 24.1

Design Code Approvals & Regulations:

- ASME, Section VIII, Division 1
- DOT-4L
- National Fies Protection Association (NFPA) 52
- Society of Automotive Engineers (SAE) J2343
- California Code of Regulations Title 13, Division 2, Chapter 4, Article 2
- Texas Administration Code, Title 16, Part 1, Chapter 13, Subchapter M



Taylor-Wharton
Since 1742
www.twcryo.com

The Americas

Phone: (281) 738-2863

Asia-Pacific & Europe

Phone: (+60 3) 5191-3003

Email

sales@twcryo.com

customerservice@twcryo.com